

Saunders[®] P345 Actuator

www.cranecpe.com

Saunders[®] P345 is a polymer based piston operated pneumatic actuator designed to provide superior performance in Bioprocess applications.

Key features include:

- 1 4.5 BAR OPERATING PRESSURE**
Energy efficiency through reduced air consumption
- 2 INDUSTRY LEADING CLOSURE PERFORMANCE**
Up to 10 bar at 100% pressure drop
- 3 30% LIGHTER CONSTRUCTION**
Lighter compared to Stainless steel actuators
- 4 ZERO MAINTENANCE**
Maintenance free plug-n-play reliable operation



Saunders® P345 Actuator

Size Range

- DN8 (0.25") – DN100 (4.00")

Modes of Operation

- Spring-to-Close
- Spring-to-Open
- Double Acting

Material of Construction

- Polymer Cover: Polyamide
- Bonnet: Stainless Steel
- Suitable for typical industry wash down regimes*

Temperature

- Max: 100°C (212°F)
- Min: -10°C (14°F)

Accessory Options

- Saunders-VUE Sensors
- Limit Open Stop (Spring-to-Close Mode)
- Positioners

Interchangeability

- Easily retrofitted on existing Saunders valves
- Unique compressor design for easy diaphragm interchangeability

Product Marking

- Catalogue Code
- Valve Size
- Mode of Operation
- Operating Pressure
- Date of Manufacture

*Non-Autoclavable

Saunders P345 (Spring-to-Close) Actuator Closure Performance				
Size	Line Pressure*		Operating Pressure	Weight (Kg) /(lbs)
	PTFE	Rubber		
DN 8 (0.25")	8 bar (116 psi)	10 bar (145 psi)	4.5 bar (65 psi)	0.4 / 0.9
DN 15 (0.50")				0.8 / 1.8
DN 20 (0.75")				1.25 / 2.9
DN 25 (1.00")				1.8 / 4.0
DN 40 (1.50")				3.0 / 6.6
DN 50 (2.00")				5.6 / 12.0
DN 65 (2.50")				9.5 / 21.0
DN 80 (3.00")				21 / 46.0
DN 100 (4.00")				29 / 64.0

* All pressures are gauge pressures. Line pressure values determined with pressure on one side of the weir only (100% pressure drop, or 100% ΔP).

* 10 bar available on request

For closure performance above 10 bar, please refer S360 Power Series

Please visit our web-based Drawings Library at: www.saundersdrawings.com for a current database of drawings in PDF, 2D DWG, and 3D STP formats.

Saunders®
Grange Road
Cwmbran, Gwent
NP44 3XX, United Kingdom
Tel.: +44 1633 486666
www.cranecpe.com

Saunders®
9860 Johnson Road
Montgomery
TX 77316 USA
Tel: +1 936 588 8360
Fax: +1 936 588 8302

Crane ChemPharma & Energy, Saunders®

Crane Co., and its subsidiaries cannot accept responsibility for possible errors in catalogues, brochures, other printed materials, and website information. Crane Co. reserves the right to alter its products without notice, including products already on order provided that such alteration can be made without changes being necessary in specifications already agreed. All trademarks in this material are property of the Crane Co. or its subsidiaries. The Crane and Crane brands logotype are registered trademarks of Crane Co. All rights reserved.